

#### DESCRIPTION

Angle hose valves are designed for use with a fire hose rack assembly, or, as a fire department outlet connection. Available in 1½" and 2½" Male NST.

#### SPECIFICATIONS

- Meets or exceeds the requirements of the NFPA 24 standard.
- Body Material CAC203.
- UL listed, FM approved.

#### CORROSION PROTECTION

Hand Wheel: Chrome plated with red paint.

#### WORKING PRESSURE AND TEMPERATURE

300 PSI rated @ 0°C to 87°C temperature rating.

#### MATERIAL SPECIFICATION

| MODEL #          | CFA 40                       | CFA 65                       |
|------------------|------------------------------|------------------------------|
| Size             | 1½"×1½"                      | 2½"×2½"                      |
| Body / Shutter   | Bronze/CAC203/<br>C3604      | Bronze/CAC203/<br>C3604      |
| Hand Wheel       | Chrome plated - Red<br>Paint | Chrome plated - Red<br>Paint |
| Inlet / Outlet   | Female NPT / Male<br>NST     | Female NPT / Male<br>NST     |
| Pressure Rate    | 300 PSI                      | 300 PSI                      |
| UL / FM approved | Yes                          | Yes                          |
| Cap & Chain      | Optional                     | Optional                     |
| a (mm)           | 90                           | 127                          |
| b (mm)           | 177                          | 224                          |
| c (mm)           | 55                           | 70                           |
| d (mm)           | 60                           | 83                           |

#### SCHEMATIC



CF-400 (SIZE 2.5" TO 12")

