

FEATURES

- Size: 4" x 2.5" x 2.5"
- Type: Straight Pattern
- Material: Brass
- Finishes: Polish Brass Polished Chrome

The Straight Pattern Fire Department Connection is UL Listed and FM Approved.

Manufactured from brass components to increase service life. The single clapper design features brass clapper and brass seats within a cast brass body. The 2-1/2 inlets are pin lug design for ease of use and compatibility with local fire service districts. Swivel gaskets included. Breakable caps or plugs should be installed to protect threads and prevent debris from being accidentally introduced into the water way.

INSTALLATION

Installation of the Fire Department Connection is achieved with readily available jobsite tools. Prior to installation make sure the proper identification sign has been installed on the nipple. Coat male threads of 4" IPS nipple liberally with a suitable pipe thread sealant such as Power Seal. Tighten FDC one full turn past hand tight. Make sure FDC is aligned according to requirements.

*** DO NOT OVER TIGHTEN. OVERTIGHTENING MAY CAUSE SEVERE STRETCHING AND POSSIBLE CRACKING OF THE OF THE FDC BODY.**

NO	PART	MATERIAL ASTM
1	Body	Brass
2	Ball Bearing	Stainless Steel
3	Coupling	Brass
4	Sealing	EPDM
5	Screw	Brass /304
6	Plug+Chain	Brass
7	Hinge Pin	Brass
8	O-Ring	EPDM
9	Clapper	Brass
10	Key Ring	304/Q235A
11	Disk	Brass

